

JIADI QPJD2 4" csőszivattyú

● TECHNICAL DATA:

- Pump

Q_{max}: 4 (m³/h)
Capacity from 1.5 to 2.5(m³/h)
Total head from 214 to 28(m)

● -Motor

Adopted the NEMA standard
Power: 0.37 to 2.2 kW(Single phase)
Power: 1.1 to 3.0 kW(Three phase)
Insulation class: B
Protection grade: IP 68
Maximum diameter: φ93mm
Highest temperature of liquid: 35°C

● PERFORMANCE TABLE:

rpm:2850 Outlet:G1¹/₄" ~ G1 ¹/₂"

Type		Motor power		Capacity and head							Dimensions		
Single phase 220-240V~ Hz50	Three phase 380-415V~ Hz50	kW	Hp	1/min m ³ /h	Head (m)							Length mm	Weight kg
					0	17	25	33	42	50	0		
100QJD205-0.37 100QHD205-0.37		0.37	0.5		34	33	32	30	28	25		632	11.1
100QJD208-0.55 100QHD208-0.55		0.55	0.75		54	52	50	45	44	40		723	12.3
100QJD210-0.75 100QHD210-0.75		0.75	1		67	65	63	60	56	50		799	14.0
100QJD212-1.1 100QHD212-1.1	100QJ212-1.1 100QH212-1.1	1.1	1.5		81	78	76	70	67	60		870	15.3
100QJD214-1.1 100QHD214-1.1	100QJ214-1.1 100QH214-1.1	1.1	1.5		94	91	88	85	78	70		921	15.7
100QJD216-1.5 100QHD216-1.5	100QJ216-1.5 100QH216-1.5	1.5	2		108	104	101	100	90	80		997	16.2
100QJD220-1.5 100QHD220-1.5	100QJ220-1.5 100QH220-1.5	1.5	2		135	130	126	120	112	100		1099	18.0
100QJD225-2.2 100QHD225-2.2	100QJ225-2.2 100QH225-2.2	2.2	3		168	163	158	150	140	125		1252	20.2
100QJD230-2.2 100QHD230-2.2	100QJ230-2.2 100QH230-2.2	2.2	3		202	195	189	180	168	150		1379	21.4
	100QJ234-3 100QH234-3	3	4		229	221	214	200	190	170		1538	25.2

